

KTX Professional Woodscrews

Technical Specification

KTX Silver

- KTX head recess
- Suitable for pozi, square, philips square, and KTX screw bits
- Super TIGHT HOLD head recess for KTX, square and some pozi drive bits. No wobbling or head slippage and minimum damage to head recess from use.
- BZP (Silver) - Internal, C1022 heat treated hardened steel
- Deep drive head recess
- Double countersunk
- Fast pull out capability due to super TIGHT HOLD head recess fit.
- 4 Angled ribs for smooth finish
- All screws accompanied by 50mm hardened steel KTX bit ideally suited for impact drivers, hammer/drill drivers and drill drivers. All M3.0 use KTX No.1 bit, all M3.5 - M5.0 use KTX No.2 bit and all M6.0 use KTX No.3 bit
- Very sharp start point for fast penetration
- Significantly reduced splitting in timber allowing close to edge fixing
- Lubricated coating for ease of entry into timber
- Suited to hardwood, softwood, MDF, plywood, Chipboard, composite
- Precision TYA-17 curved cut
- Helical thread cut
- Coarse thread
- Precision manufactured
- Flat head
- High shear strength for KTX Silver – M3.0 = 3.4KN, M3.5 = 4.1 KN, M4.0 = 5.1KN, M4.5 = 6.2KN , M5.0 = 7.3KN , M6.0 = 10.5KN
- All KTX screws are CE rated EN:14592